

B10 SERIES



The thirst quenchers!™

**3 YEAR
WARRANTY**



- ✓ Floor Standing or Counter Top
- ✓ Designed to fit the Waterworks™ Aquanet® Filter, Self-Fill Bottle, or standard water bottles
- ✓ Lead Free Waterways
- ✓ Stainless Steel Reservoir
- ✓ Wide Removable Drip Tray
- ✓ Available in Cool & Cold or Hot & Cold
- ✓ Easily converts from bottle top to POU. Conversion kit available
- ✓ Cloud White Finish
- ✓ 36 month Comprehensive Warranty

**PROVEN
QUALITY &
PERFORMANCE
FOR OVER 20
YEARS!**

B10 SERIES

GENERAL FEATURES

The Waterworks™ B10 series cooler with its stylish design and durability is the only cooler on the market that can be converted into a plumbed unit.

COLD TANK: Hygienic 3.2 litre 304 stainless steel tank for superior chilling. The highly polished surface is easy to clean and maintain

HOT TANK: 1.8 litre type 304 stainless steel tank with 500 watt sheathed heater ensure temperature control. On/off switch is easily accessible at the back of the cabinet

CABINET: Gloss white in colour. Top and front panels are moulded UV treated ABS and side panels are zinc coated steel sheets covered in polymer polyester resin

TAPS: NSF approved durable polypropylene self-closing design. Fully recessed, lever type with fast flow. Hot safety tap comes as standard on hot/cold model. Optional push taps now available

OPTIONAL EXTRAS

POU CONVERSION KIT: This easily installed POU Kit turns your bottled water cooler in to a mains connected unit.

SELF-FILL BOTTLE: A flexible filtration option for home, office or factory. Just fill with tap water for a continuous supply of fresh water. The SFB is the perfect partner for all bottled coolers and ceramic dispensers.

NON SPLASH VALVE: Allows the bottle to be changed without excess spillage. Just place the bottle on the cooler and the valve opens to let water through. When removing the bottle, the valve automatically closes.

SPECIFICATIONS

REFRIGERATION: Gas R134A. Refrigerant flow is controlled by capillary tube which has no moving parts. The compressor is hermetically sealed with automatic overload protection. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled static type with no moving parts.

PERFORMANCE

Tap 1 Approx. 4-10°C.

Tap 2 Room temperature.

Hot Tap Approx. 84-89°C.

CAPACITY

ROOM TEMP °C	21	27	32
150ML CUPS/HR 10°C	44	32	18
LITRES/HR AT 10°C	4.2	3.1	1.8
Hot WATER DELIVERY: 45 x 170ml cups per hour			

*Intermittent use only, continuous use will result in reduced performance.

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
B10C	17kg	B10CH	19kg	33cm	33cm	100cm

QUALITY: The specifications of these coolers are manufactured to comply with the standards of underwriters laboratories.

WARRANTY

The range of Waterworks™ B10 Series water coolers are covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage, for the period of 36 months from the date of original sale.



Waterworks™ Australia

ABN 91 902 793 936

48-50 Neumann Road Capalaba Queensland 4157

Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157

As part of Waterworks™ Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.

Distributed by...

Phone (07) 3390 3777

Email sales@waterworksaustralia.com

www.waterworksaustralia.com