D10 SERIES

(Viaterworks.)



The thirst quenchers!™



- Easily converts from bottle top to POU, conversion kit available
- Available in Hot/Cold or Cool/Cold
- Cloud White finish
- ✓ 3.2 litre stainless steel cold tank
- Connects to mains water supply
- Compatible with most Inline Filter Systems
- Lead free Waterways
- 36 Month Comprehensive Warranty

PROVEN QUALITY & PERFORMANCE FOR OVER 20 YEARS!

D10 SERIES

GENERAL FEATURES

The Waterworks^M D10 is one of the only coolers on the market that can be easily converted from bottle to POU and has been a favourite in the rental industry for over 20 years!

COLD TANK: 3.2 litre type 304 stainless steel for superior chilling. The highly polished surface is easy to clean and maintain.

HOT TANK: 1.8 litre type 304 stainless steel with 500 watt sheathed heater ensures temperature control. On/ off switch is easily accessible at the back of the unit.

CABINET: Gloss white colour. Top and front panels are treated ABS plastic. The side panels are zinc coated steel covered in polymer polyester resin.

TAPS: NSF approved durable polypropylene self-closing design. Fully recessed, lever type with fast flow. Hot safety tap comes as standard on Hot/Cold models. Optional push taps now available.

POU CONVERSION KIT: The easily installed POU Kit turns the bottle top cooler (B10) in to a mains connected unit. Can also convert back to bottle top.

OPTIONAL EXTRAS

PNP FILTER SYSTEM: The Waterworks[™] PNP filter range is available in single, twin or triple. With the swing & twist design and automatic water shutoff, filter changes are simple, no need for tools or to turn off the mains water.

CD2 - **CUP DISPENSER:** The CD2 is perfectly colour matched to suit the B5, B10, D5 & D10 coolers. Waterworks[™] paper & plastic cups are made to fit the CD2.

INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled with no moving parts.

PERFORMANCE

Tap 1Approx. 4-10°CTap 2Room TemperatureHot tapApprox. 84-89°C

CAPACITY

ROOM TEMP °C	21	27	32			
150ML CUPS/HR 10°C	22	17	13			
LITRES/HR AT 10°C	3.2	2.6	2			
HOT WATER DELIVERY: 15 x 170ml cups per hour						

*Intermittent use only, continuous use will result in reduced performance.

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
D10C	17kg	D10CH	19kg	33cm	33cm	120cm

WARRANTY

The Waterworks[™] D10 series are covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.



Waterworks[™] Australia ABN 91 902 793 936

48-50 Neumann Road Capalaba Queensland 4157 Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157 Distributed by...

Phone (07) 3390 3777

Email sales@waterworksaustralia.com www.waterworksaustralia.com

As part of Waterworks[™] Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.