

IC8

REMOTE UNDERSINK CHILLER



The thirst quenchers!™



Lead and copper free waterways



1.9 litre stainless steel
chilling tank



8 Litres/hour
cooling capacity



Stainless steel
internal waterways



Powder coated corrosion
resistant cabinet



8 cup initial draw-off



Dual, fan assisted
static condensers



3 year comprehensive
warranty



Easy to install



IC8

REMOTE UNDERSINK CHILLER



"The thirst quenchers!"

With its 8 litre per hour cooling capacity, the Waterworks™ IC8 is proof that good things come in small packages. Due to the compact design, energy efficiency and quiet operation the IC8 Under-sink chiller is the obvious choice for household applications and offices alike.



SPECIFICATIONS



CABINET: The cabinet is a corrosion resistant, high polymer polyester coated steel panel.



COLD WATER TANK: 1.9 litre fully insulated, 304 stainless steel tank. The drain plug and seal are removable for servicing.



REFRIGERATION SYSTEM: This fan assisted, static condenser system utilises R134a refrigerant which is non toxic, non-flammable and non ozone depleting. Refrigerant flow is controlled by capillary tube, which has no moving parts. The compressor is protected by an automatic overload, is lifetime lubricated and hermetically sealed.



INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.



INSTALLATION



GENERAL: The Waterworks™ IC8 can be installed in small spaces with adequate ventilation, and can be used in conjunction with most inline filter systems. The IC8 must be professionally installed with either a vented tap or with the included kit which contains a pressure reducing valve (PRV), pressure limiting valve (PLV), shutoff valve, stainless steel connectors and a drain clamp.



PLUMBING CONNECTIONS: Both the inlet and outlet are recessed 1/4" stainless steel pipes. Quick connect stainless steel fittings are included in the above mentioned installation kit.



ELECTRICAL: Certificate number 202240. 220-240v 50hz single phase. Full load current is .8 amps. 1.5 metre power cord is supplied.



COOLING PERFORMANCE: 8 litres per hour at 8-10°C
Cooling Speed: From 27°C to 8°C in 20 minutes
Draw Off Capacity: 8 cups (150ml) below 10°C



As part of Waterworks™ Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.



WEIGHTS & DIMENSIONS

IC8	WEIGHT	WIDTH	DEPTH	HEIGHT
NETT	12.5kg	21cm	41cm	28cm
PACKED	14kg	23cm	46cm	30cm



WARRANTY

The Waterworks™ IC8 under sink chiller is covered by a 3 year comprehensive warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 3 years from the date of original sale.

Distributed by...

Waterworks™ Australia
ABN 91 902 793 936



48-50 Neumann Road Capalaba Queensland 4157
Bulk Warehouse: 53 Neumann Road
Capalaba Queensland 4157



Phone (07) 3390 3777



Email sales@waterworksaustralia.com



www.waterworksaustralia.com

