SB5 series

- POWER



- HOT - COLD



The thirst quenchers!™



Floor Standing or Counter Top

- Available as Cool & Cold or Hot & Cold
- ✓ Designed to fit the Waterworks™ Aquanet® Filter, Self-Fill Bottle, or standard water bottles
- Lead Free Waterways
- Stainless Steel Reservoir
- Wide removable
 Drip Tray and Grid
- Cloud White Finish
- 36 month Comprehensive Warranty

SB5 series

GENERAL FEATURES

The SB5 series has been our leading bottle top cooler for over 20 years and is still a favourite.

"Copied" by many but none have been able to equal or better the quality and longevity of the Waterworks™ SB5.

COLD TANK: 4 litre hygienic 304 stainless steel, for superior chilling. The highly polished surface is easy to clean and maintain

HOT TANK: 1.8 litre hygienic type 304 stainless steel tank with 500 watt sheathed heater to ensure temperature control. The on/off switch is easily accessible at the back of the unit

CABINET: Gloss Cloud White in colour. The top and front panels are moulded UV treated ABS. The side panels are made from zinc coated steel sheets covered in polymer polyester resin.

TAPS: NSF approved durable polypropylene self-closing design. Fully recessed lever type for fast flow. Hot safety tap comes as standard on hot/cold model. Optional hands free push taps now available.

OPTIONAL EXTRAS

SELF-FILL BOTTLE: A flexible filtration option for home, office or factory. Just fill with tap water for a continuous supply of fresh water. The SFB is the perfect partner for all bottled coolers and ceramic dispensers.

AQUANET: The Waterworks[™] AN1 is specifically designed for our SB5 series coolers. Simply remove the no-spill spike and replace with a scuff ring (SR5) to provide a base for the AN1 and bottle. Ask us about the no-splash valve which is ideal for this set up.

NON SPLASH VALVE: Allows the bottle to be changed without excess spillage. Just place the bottle on the cooler and the valve opens to let water through. When removing the bottle, the valve automatically closes.

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps

CONDENSER: Quietly operating, air cooled static type with no moving parts

PERFORMANCE

Tap 1	Approx.	4-8°C
-------	---------	-------

Tap 2 Room Temperature

Hot tap Approx. 84-87°C

CAPACITY

ROOM TEMP °C	21	27	32			
150ML CUPS/HR 10°C	44	32	18			
LITRES/HR AT 10°C	4.2	3.1	1.8			
HOT WATER DELIVERY: 45 x 170ml cups per hour						

HOT WATER DELIVERY: 45 x 170ml cups per hour

*Intermittent use only, continuous use will result in reduced performance.

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
SB5C	16kg	SB5CH	18kg	33cm	33cm	60cm

WARRANTY

The entire range of Waterworks[™] SB5 Series water coolers are covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.

Damage to the stainless steel tank may occur if using reverse osmosis or incorrect filtration.

Warranty will be void in the event of this happening.

Please discuss filtration options with your local water filter specialist.



Waterworks[™] Australia ABN 91 902 793 936

48-50 Neumann Road Capalaba Queensland 4157 Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157 Distributed by...

Phone (07) 3390 3777

Email sales@waterworksaustralia.com www.waterworksaustralia.com

As part of Waterworks[™] Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.